

## **Solutions for Your Spray Foam Operation**

PRODUCT NAME	PRODUCT DESCRIPTION	COMMON USES	COMPATIBLE ELASTOMERS
Chem-Trend∘ SprayFoam Silicone	Blend of silicones and specialized parting agents specifically designed to prevent spray polyurethane foam insulation from adhering to most surfaces.	Preventative spray coating for a variety of hard surfaces to protect and prevent overspray from sticking.	
Chem-Trend MOC-10014	Excellent low hazard cleaner that attacks resinous buildup to remove it from spray foam tanks and equipment. Formerly known as Flush 1.	Preventative, daily flush applications.	Neoprene, Silicone, Ethylene Propylene Polymers, Styrene, Butadiene, Natural Rubber, Polypropylene, Epoxy, Teflon, Nylon 6,6 Resistance of any material will vary depending on elastomer source and contact time. Test before use.
Chem-Trend∘ FC-10008	A multipurpose product, it can be used to purge liquid isocyanates in the first step of the flush process and is an excellent choice for storage oil.	•Use to purge liquid ISO from supply lines and equipment. Effective as a storage oil fluid.	Neoprene, Silicone, Ethylene Propylene Polymers, Styrene, Butadiene, Natural Rubber, Polypropylene, Epoxy, Teflon, Nylon 6,6 Resistance of any material will vary depending on elastomer source and contact time. Test before use.
Chem-Trend SprayFoam Flush 4	Powerful flushing solvent and cleaner for spray polyurethane foam mixing and metering equipment. Designed to remove polyurethane components from metal and plastic surfaces.	• Removes cured resin from ISO tank, hoses, metering equipment, and guns. • Hardened ISO is the primary reason for cleaning. • Often requires extended circulation.	Buna, Fluoroelastomer (FKM), Hastelloy C, Nylon, PTFE, PVDF Resistance of any material will vary depending on elastomer source and contact time. Test before use.
Chem-Trend® MOC-10009	Powerful flushing solvent and cleaner with a citrus scent for spray polyurethane foam mixing and metering equipment. Designed to remove polyurethane components from metal and plastic surfaces.	Removes cured resin from ISO tank, hoses, metering equipment, and guns.   Hardened ISO is the primary reason for cleaning.   Often requires extended circulation.	PFE, Viton, Flourosilicone, EPDM Resistance of any material will vary depending on elastomer source and contact time. Test before use.
Chem Trend® SprayFoam Remover	Powerful stripping agent that attacks SprayFoam foam. The most effective, easy-to-handle foam urethane resin remover available, this product is completely soluble with water and most organic solvents.	• Excellent tool and equipment cleaner. Commonly used in a soak tank allowing for complete immersion of the item that needs to be cleaned. • Remover has been used as a flush cleaner as well, especially for heavy duty soil loads. • Recommended for bare metal surfaces. • Note: Do not use Chem-Trend· SprayFoam Remover for cleaning polymeric (plastic) or painted surfaces unless the surface has been carefully checked for resistance. Chem-Trend·SprayFoam Remover will also strip clear coat and/or painted finishes.	Perfluoro elastomer, Viton® ETP, Aflas® TFE/P, Viton® FKM, Buna-N NBR, Silicone, Fluoro Silicone Resistance of any material will vary depending on elastomer source and contact time. Test before use.



