




Product Data Sheet

Chem-Trend® SprayFoam Release Wipes

KEY FEATURES



REDUCES
CLEANING TIME



MINIMIZES
WASTE



LOWERS
V.O.C.S

PRODUCT DESCRIPTION

Chem-Trend® SprayFoam Release Wipes is a blend of silicones and specialized parting agents that are specifically designed to prevent spray polyurethane foam insulation from adhering to most surfaces where the product is applied.

Chem-Trend® SprayFoam Release Wipes acts as an effective barrier coat to keep overspray of polyurethane foam insulation from adhering to items such as spray equipment, tub & shower stalls, and other non-porous surfaces.

APPLICATION

1. Thoroughly clean the application surface with a Chem-Trend cleaner to remove excessive amounts of dirt and contaminants. Wipe dry with a clean cloth or towel.
2. Use Chem-Trend® SprayFoam Release Wipes to apply to non-porous surfaces where spray foam over spray may come in contact with.
3. Do not reuse discarded wipes.

STORAGE

Store product between 5C and 30C (41F and 86F). Shelf life is 18 months from the date of manufacture, in the original unopened container. When using pre-saturated wipes, make sure that the container lid closes securely in place so that evaporation does not occur to the remaining wipes. Product must be kept in the original container and the lid replaced immediately after dispensing. Outside of the container, pre-saturated wipes should be used within 10 minutes. After opening, product should continue to be stored properly.

HANDLING

We believe Chem-Trend® SprayFoam Silicone has a low degree of hazard when used as intended. For more information, request a copy of Chem-Trend's Material Safety Data Sheet.

PACKAGING

100 Wipes per can
6 Cannisters per case
Refill packs (Wipes only) Sold Separately



RECOMMENDED USE

Applications Rigid spray polyurethane insulation foam

Recommended Temperature Range, °F/°C Ambient room temperature

FURTHER INFORMATION

Request information on our complete range of materials: custom-formulated release agents for polyurethane molding; tire lubes and bladder coatings; Mono-Coat® semipermanent release coatings; aerosol formulations; mold cleaners and sealers; specialized coatings and application equipment. While the technical information and suggestions for use contained herein are believed to be accurate and reliable, nothing stated in this bulletin is to be taken as a warranty either expressed or implied.

For more information visit here:

